



Technical data				
Specification	1.1	Manufacturer's type designation		XT250
	1.2	Drive		Electric
	1.3	Operating type		Seat-on
	1.4	Load capacity	Q (t)	25
	1.5	Rated drawbar pull	F (KN)	13
	1.6	Wheelbase	Y (mm)	1850
Weight	2.1	Dead weight	(kg)	4530
	2.2	Axle loading, laden front/rear	(kg)	—
	2.3	Axle loading, unladen front/rear	(kg)	2100 /2430
Tyres/chassis	3.1	Tyres		Polurethane
	3.2	Tyre size, front	Ø x w(mm)	6.50-10-10PR
	3.3	Tyre size, rear	Ø x w(mm)	7.00-15-12PR
	3.4	Additional wheels (dimensions)	Ø x w(mm)	—
	3.5	Wheels, number front/rear (x = driven wheels)		2/2x
	3.6	Tread , front	b10 (mm)	1250
	3.7	Tread , rear	b11 (mm)	1230
Dimension	4.1	Height of overhead guard(cabin)	h6 (mm)	2250
	4.2	Seat height relating to SIP/stand height	h7 (mm)	1100
	4.3	Height of tiller in drive position min. / max	h14 (mm)	—
	4.4	Coupling height	h10 (mm)	304.8/400
	4.5	Overhang	l5 (mm)	800
	4.6	front overhang	b9 (mm)	655
	4.7	Overall length	l1 (mm)	3355
	4.8	Overall width	b1/b2 (mm)	1450
	4.9	Ground clearance, centre of wheelbase	m2 (mm)	120
	4.10	Turning radius(min)	Wa (mm)	3500
Performance	5.1	Travel speed, laden/unladen	(km/h)	10/20
	5.2	Travel speed, laden/unladen, backwards	(km/h)	—
	5.3	Drawbar pull,laden/unladen	(KN)	13
	5.4	Max. drawbar pull, laden/unladen	(KN)	18
	5.5	Gradeability, laden/unladen	(%)	5/25
	5.6	Service brake		Hydraulic
Electric -engine	6.1	Drive motor rating S2 60 min	(kW)	23
	6.2	Battery according to DIN 43531/35/36 A,B,C,no		Special case
	6.3	Battery voltage/nominal capacity K5	(V/Ah)	80/630
	6.4	Battery weight	(kg)	1615
Addition	7.1	Type of drive control		AC
	7.2	Sound pressure level at the driver's seat according to EN 12053	dB (A)	< 70
	7.3	Towing coupling, type DIN 15170		Bolt type

# XT250

Meet your needs for transporting heavy duty goods

